

## THREADED NOZZLES AVAILABLE FROM STOCK


### CUSTOMISED MARKING AND PACKING – SHORT DELIVERY TIME!

**Dimensional standards:**

- SAIPEM / SNAMPROGETTI TB.HPU.5002 - TB.5002
- UREA CASALE 8577-00-SDP-009 – 000-00-SDP-009

**Material grades:**

- ASTM A182 – F 316L UREA GRADE MODIFIED
- ASTM A182 – F310 MoLN / 25.22.2 / UNS S31050



DNP	A	B	F	L	Z	S	Mass
	<b>External diameter</b>	<b>Internal diameter</b>	<b>Contact diameter</b>	<b>Thread length</b>	<b>Total length</b>		<b>Kg</b>
<b>1/4"</b>	13.7	6.0	10.5	40	100	To suit pipe wall thickness	0.1
<b>1/2"</b>	21.3	11.3	18.0	40	100		0.2
<b>3/4"</b>	26.7	14.7	22.0	40	100		0.2
<b>1"</b>	33.4	19.2	29.5	55	100		0.4
<b>1.1/2"</b>	48.6	30.5	43.5	55	100		0.7
<b>2"</b>	60.3	39.3	53.0	70	100		1.2
<b>3"</b>	88.9	58.4	79.0	90	150		3.6
<b>4"</b>	114.3	77.2	103.0	110	150		5.7
<b>6"</b>	168.3	116.4	152.0	135	150		11.8
<b>8"</b>	219.1	153.1	196.0	160	180		23.5
<b>10"</b>	273.0	190.4	241.0	170	200		47.3
<b>12"</b>	323.8	228.0	292.0	220	260		86.3

Please contact our commercial department to check quantities available!

[meccanica@meccanicapadana.com](mailto:meccanica@meccanicapadana.com)

